



1,6 GHz
up to
2,6 GHz

4 GB RAM
32 GB SSD

1 x DP
2 x HDMI

2 x USB 3.0
4 x USB 2.0

2 x RJ/45
LAN

external
Power supply

RT-401

Reliable, stylish and efficient.

Our entry-level model, the Rangee RT-401, impresses with its cost-effective efficiency and attractive design. Equipped with solid technology, it offers a reliable solution for everyday tasks. Discover the optimal balance between affordability and performance for a smooth working environment.

| Products | | |
|----------|----------|------------------|
| | SKU | Operating system |
| RT-401 | 21101727 | without |
| RT-401-L | 21119727 | RangeeOS |

System

| | |
|-----------|----------------------------|
| Processor | Intel J3710, 1,6 - 2,6 GHz |
| RAM | 4GB DDR3 SO-DIMM |
| Flash | 32GB SATA Flash |

Graphic

| | |
|--------------------|--|
| Maximum resolution | 2 x 2560x1440@60Hz 3 x 1920x1080@60Hz |
|--------------------|--|

| | |
|-------|------------------|
| Ports | 1 x DP, 2 x HDMI |
|-------|------------------|

Audio

| | |
|-------|------------------------|
| Ports | 1 x 2 in1 Audio In-Out |
|-------|------------------------|

Interfaces

| | |
|-----|--------------------------|
| USB | 4 x USB 2.0, 2 x USB 3.0 |
|-----|--------------------------|

| | |
|-----|---------|
| COM | 1 x COM |
|-----|---------|

Network

| | |
|----------|--------------------------------------|
| Ethernet | 2 x 100/1000 Mbit LAN RJ/45 Ethernet |
|----------|--------------------------------------|

| | |
|--------------|------------------------|
| Wireless LAN | Support for USB sticks |
|--------------|------------------------|

Device

| | |
|------------|-------------------|
| Dimensions | 134 x 126 x 22 mm |
|------------|-------------------|

| | |
|--------|-------|
| Weight | 0,7kg |
|--------|-------|

| | |
|---------|---------------------|
| Cooling | fanless, convection |
|---------|---------------------|

| | |
|-----------------------|---------------------------|
| Operating temperature | 5° - 95°C, non-condensing |
|-----------------------|---------------------------|

Power

| | |
|--------------|--------------------------------|
| Power supply | external power supply 12V 1,5A |
|--------------|--------------------------------|

| | |
|-------------------|--|
| Power consumption | 110-220V 6 Watt power consumption (idle) |
|-------------------|--|

Features

| | |
|----------|---|
| Warranty | 3 years Bring-In incl. Advance exchange, within the first month from purchase, extendable up to 5 years |
|----------|---|

| | |
|------------|----------------------|
| VESA mount | optionally available |
|------------|----------------------|

| | |
|-------------------|-------------------------|
| Remote Management | via Webbrowser and TCMS |
|-------------------|-------------------------|

| | |
|------------------|------------------------|
| Operating System | RangeeOS (linux based) |
|------------------|------------------------|

Front

01



Back

02



Vesa mount

03



Accessories

| | | |
|----------|--------------------------|--|
| 15000081 | 5 Jahre Bring-In | 5 years warranty extension w. Bring-In service |
| 15000082 | 5 years Advance exchange | 5 years warranty extension w. advance exchange service |
| 22920027 | VESA mount | VESA mount 75/100 |

FREE DEMO
RANGEE.COM/FREE-DEMO